

# Carrier Model # 06CC Physical and Electrical Specifications

MODEL	06CC	016	018	124	228	337	550	665	675	899
NET OIL PRESSURE		12-22	12-22	12-22	12-22	12-22	12-22	12-22	12-22	12-22
CYLINDERS		6	6	6	6	6	6	6	6	6
BORE		2	2	2	2	2	2-11/16	2-11/16	2-11/16	2-11/16
STROKE		1-1/4	1-1/4	1-1/4	1-15/32	1-15/16	2-3/16	2	2-3/16	2-7/8
DISPLACEMENT CFM		15.9	18.3	23.9	28	37.1	50.3	65	75.4	99.0
OIL GRADE		150	150	150	150	150	150	150	150	150
OIL CHARGE	PINTS	10	10	10	10	10	19	19	19	19
NET WEIGHT		335	335	335	340	345	545	555	555	580
RATED BTUH X 1000	R-12	15° F								
	R-22	40° F	17.6	22.6	24.6	29.5	39.9	56.3	71.4	80.6
	R-502	-25° F								
	R-502	20° F								
MOTOR SIZE	HP	5	5	6.5	7.5	10	15	20	20	30
ELECTRICAL DATA										
208-230 -3- 60	LRA XL	100.0	100.0	160.0	198.0	228.0	283.0	345.0	345.0	506.0
	MAX RLA	19.3	19.3	23.6	29.7	33.2	36.0	60.7	60.7	82.9
	MTA	27.0	27.0	33.0	41.6	46.5	52.0	85.0	85.0	130.0
460 -3- 60	LRA XL	50.0	50.0	80.0	99.0	114.0	142.0	173	173.0	253.0
	MAX RLA	9.6	9.6	11.8	14.9	16.6	18.6	25.7	30.0	45.0
	MTA	13.5	13.5	16.5	20.9	23.3	26.0	42.0	42.0	65.0
575 -3- 60	LRA XL	40.0	40.0	64.0	79.0	91.0	98.0	120.0	120.0	176.0
	MAX RLA	7.7	7.7	9.4	11.9	13.4	14.3	19.3	26.4	35.7
	MTA	10.8	10.8	13.2	16.7	18.8	21.0	33.0	33.0	52.0

Conditions: R12, 15° SST, 110° SCT, 65° RGT  
R22, 40° SST, 120° SCT, 60° RGT  
R502, -25° SST, 110° SCT, 65° RGT  
R502, 20° SST, 120° SCT, 65° RGT