

Trane Model E & F Open Drive Physical Specifications

MODEL	3E	40	50	60	80	MODEL	F/3F	30	40	50	60	80
	OPEN DRIVE R-22						OPEN DRIVE 'F' MODEL					
NET OIL PRESSURE	75	75	75	75	75	NET OIL PRESSURE	75	75	75	75	75	75
CYLINDERS	4	5	6	8	8	CYLINDERS	3	4	5	6	8	8
BORE	3.66	3.66	3.66	3.66	3.66	BORE	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
STROKE	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	STROKE	2	2	2	2	2	2
DISPLACEMENT CFM	117.2	146.5	175.8	234.4	234.4	DISPLACEMENT CFM	36.1	48.1	60.2	72.2	96.2	96.2
OIL GRADE	300	300	300	300	300	OIL GRADE	300	300	300	300	300	300
OIL CHARGE PINTS	29	31	31	33	33	OIL CHARGE PINTS	13-1/2	18	19	19	19	20-1/2
NET WEIGHT	784	884	916	1005	1005	NET WEIGHT	415	485	520	525	575	575
RATED BTUH X 1000						RATED TONS	R-12	10	13	17	19	20-1/2
	R-22	48.5	60.4	72.8	98.8		R-22	15	20	25	30	40
MOTOR SIZE	BHP	63.5	78.7	94.8	128	MOTOR SIZE	BHP					