



York Model # JS & JG Physical Specifications

www.AmericanHermetics.net - 800-240-9200

MODEL	JS/JG	43	53	63	73	83
NET OIL PRESSURE		60*	60*	60*	60*	60*
CYLINDERS		4	5	6	7	8
BORE		3-3/4	3-3/4	3-3/4	3-3/4	3-3/4
STROKE		3.2	3.0	3.0	3.1	3.1
DISPLACEMENT CFM		143.2	167.8	201.3	242.7	277.4
OIL GRADE		300	300	300	300	300
OIL CHARGE	GALS.	3	3*	3*	3*	3*
NET WEIGHT		1370	1480	1480	1640	1640
RATED	R-12	X	X	X	X	X
TONS	R-22	X	X	X	X	X
<p>* Styles A through D oil pressure should be 25 - 40 PSI above Suction. Style E, F, & JG should have a minimum of 60 PSI.</p> <p>* Styles A through D, 5 through 8 cylinder, 3-1/2 gallon oil charge. Styles E, F, & JG, 3 Gallons, all compressors.</p>						
MODEL	JS/JG	44	54	64	74	84
NET OIL PRESSURE		60*	60*	60*	60*	60*
CYLINDERS		4	5	6	7	8
BORE		3-3/4	3-3/4	3-3/4	3-3/4	3-3/4
STROKE		3.8	3.6	3.6	3.7	3.7
DISPLACEMENT CFM		170.0	201.3	241.6	289.7	331.1
OIL GRADE		300	300	300	300	300
OIL CHARGE	GALS.	3	3*	3*	3*	3*
NET WEIGHT		1370	1480	1480	1640	1640
RATED	R-12	X	X	X	X	X
TONS	R-22	X	X	X	X	X